



# Haskel

MILTON ROY

# Mini Sport Booster

## 4" DRIVE AIR DRIVEN GAS BOOSTER

**For Charging O2 Cylinders for Rebreathers and any other O2 Applications**

The Mini Sport Booster has been designed and manufactured to achieve the ideal product for the dive market, providing performance and reliability at an affordable price.

### FEATURES

- Charges Gases Up To 3,300 PSIG (227.53 BAR)
- Inlet Gas Pressures as low as 100 PSIG (6.89 BAR)
- Lightweight Portability
- Locking Speed Control Muffler
- Relief Valve for Integrated Air Drive Protection
- Integrated Cooling Jacket and Distance Piece for Extended Seal Life and Total O2 Separation.

### SPECIFICATIONS

DRIVE:	4 INCHES
RATIO:	25:1
WEIGHT:	12 LBS
MAX RATED INLET PRESSURE	4,500 PSI (310.26 BAR)
MAX RATED OUTLET PRESSURE	4,500 PSI (310.26 BAR)
VOLUME PER CYCLE:	1.232 CU. IN. (.0202 LITER)
MAXIMUM PRESSURE OUTPUT:	3,300 PSI (227.53 BAR)
MINIMUM GAS SUPPLY PRESSURE:	100 PSI (6.89 BAR)

### FILL TIMES

FILL TARGET PRESSURE	2400	3000
	PUMP-UP TIME AFTER EQUALIZATION TO 19 CU FT TANK (MIN:SEC)	
GAS SUPPLY PRESSURE (PSI)		
500	4:31	6:00
1000	1:44	3:00
1500	0:33	1:31
2000	0:12	1:00
2400	0:00	0:32

\* Gas Supply from a single 80 Cu Ft bottle




**XTREME SCUBA**  
 TECHNICAL DIVE CENTER  
 xtremescuba.com

**SPECIFICATION:**

DRIVE: 4 INCHES

RATIO: 25:1

WEIGHT: 12 LBS (5.44 KG)

MAXIMUM RATED INLET PRESSURE: 4,500 PSI (310.26 BAR)

MAXIMUM RATED OUTLET PRESSURE: 4,500 PSI (310.26 BAR)

VOLUME PER CYCLE: 1.232 CU. IN. (0.0202 LITER)

MAXIMUM PRESSURE OUTPUT: 3,300 PSI (227.53 BAR)

MINIMUM GAS SUPPLY PRESSURE: 100 PSI (6.89 BAR)

# ***MICRO BOOSTER*** **(4AG-25)**

